



2018
CFMOTO CFORCE 500 HO EPS LX
(2 UP)

STARTING AT
\$8,195*

Best 5 Year
(LIMITED)
Warranty**

CFMOTO.CA

WIND
ZONE
windzone.ca

2018 CFMOTO CFORCE 500 HO EPS LX (2 UP)



**GET IT ALL! PRICE, WARRANTY,
THE BEST FEATURES
& ADVENTURE!**



ORANGE

**CFORCE
500 HO**

METALLIC BLUE
ROYAL BLUE

TITANIUM GREY

**Best 5 Year
(LIMITED)
Warranty****

STANDARD FEATURES AND BENEFITS

SAFETY

A-arm protectors / Lateral mirrors / Horn
Halogen hi & low beam / Hazard lights / Flashers

LOOK

High quality graphics / Premium glossy paint

CONVENIENCE

Trailer connector / Passenger backrest / Storage back driver seat
Hitch receiver / 12V plug / Winch (2500 lb)

DURABILITY

Skid plate / Steel front bumper
Rear bumper / Extended Fender

LCD DASHBOARD

Digital information center with a KM/MPH odometer and a multi-function gauge: RPM, speed, tachometer, gear position, temperature, engine light, fuel level and a clock.



ENGINE

| | |
|----------------------|--------------------------|
| TYPE | Single-Cylinder, 4-valve |
| DISPLACEMENT | 495 cc |
| BORE & STROKE | 91 x 76.2 mm |
| COMPRESSION | 10.3 : 1 |
| ENGINE MANAGEMENT | BOSCH EFI & Ignition |
| MAXIMUM TORQUE | 34 FT/LB @ 5800 rpm |
| MAXIMUM POWER OUTPUT | 37.5 HP / 6800 rpm |
| COOLING SYSTEM | Liquid |
| STARTING | Electric |
| BATTERY | 30 Amp |

SIZE / WEIGHT

| | |
|--------------------------|---|
| LENGTH x WIDTH x HEIGHT | 2350 x 1160 x 1400 mm (92.5 x 45.7 x 55.1 in) |
| WHEELBASE | 1480 mm (58.3 in) |
| SEAT HEIGHT | 530 mm (20.9 in) |
| GROUND CLEARANCE | 270 mm (10.6 in) |
| FUEL TANK CAPACITY | 18 L (4.75 gal) |
| CURB WEIGHT | 375 kg (826 lb) |
| TOWING CAPACITY | 150 kg (330 lb) |
| FRONT/REAR RACK CAPACITY | 20 kg (44 lb) / 40 kg (88 lb) |

TRANSMISSION

| | |
|---------------------------|---|
| CV-TECH IBC clutch system | Primary and secondary variable transmission Gear box: L / H / N / R / P (parking lock shift system) |
| POWER TRAIN | 2 wheel / 4 wheel drive, electric locking differential |



WHEELS

| | |
|--------------|---|
| FRONT WHEELS | Aluminium Black rims (12 x 6) |
| REAR WHEELS | Aluminium Black rims (12 x 7.5) |
| FRONT TIRES | AT 25 x 8-12 (Innova Mud Gear Lite 6 ply rating) |
| REAR TIRES | AT 25 x 10-12 (Innova Mud Gear Lite 6 ply rating) |

SUSPENSION AND STEERING

| | |
|------------------|---|
| FRONT SUSPENSION | Double wishbone independent suspension Hydraulic shock absorber, five adjustments spring preloads |
| TRAVEL | 203 mm (8 in) |
| REAR SUSPENSION | Double wishbone independent suspension Hydraulic shock absorber, five adjustments spring preloads |
| TRAVEL | 231 mm (9.1 in) |
| STEERING | Electronic Power Steering (EPS) |

BRAKES

FRONT AND REAR BRAKE DISC SYSTEM

