

2018  
**CFMOTO UFORCE 500 HO**

STARTING AT  
**\$9,595\***



**Best 5 Year**  
(LIMITED)  
**Warranty\*\***

**CFMOTO.CA**

**WIND**  
**ZONE**   
**windzone.ca**



# 2018 CFMOTO UFORCE 500 HO

(UFORCE 500 HO EPS LX also available)



**GET IT ALL! PRICE, WARRANTY,  
THE BEST FEATURES  
& ADVENTURE!**



ORANGE

TITANIUM GREY

**Best 5 Year  
(LIMITED)  
Warranty\*\***

## STANDARD FEATURES AND BENEFITS

### SAFETY

Passenger hold bar | Side Doors | Lateral mirrors | Horn  
ROPS certified Roll Cage | 3 points Seat belts | Hand brake  
Halogen hi & low beam | Hazard lights | Flashers

### LOOK

High quality graphics | Premium glossy paint

### CONVENIENCE

Trailer connector | Adjustable & lockable steering | Cup holders  
Storage under hood | Glove compartment | Hitch receiver  
12V plug | Adjustable driver seat | LX model: Winch (3500 lb)

### DURABILITY

Skid plate | Stainless steel exhaust system | Steel front bumper

### LCD DASHBOARD

Digital information center with a KM/MPH odometer and a multi-function gauge: RPM, speed, tachometer, gear position, temperature, engine light, fuel level and a clock.



## ENGINE

TYPE	Single-Cylinder, 4-valve
DISPLACEMENT	495 cc
BORE & STROKE	91 x 76.2 mm
COMPRESSION	10.3 : 1
ENGINE MANAGEMENT	BOSCH EFI & Ignition
MAXIMUM TORQUE	34 FT/LB @ 5800 rpm
MAXIMUM POWER OUTPUT	37.5 HP / 6800 rpm
COOLING SYSTEM	Liquid
STARTING	Electric
BATTERY	30 Amp

## SIZE / WEIGHT

LENGTH x WIDTH x HEIGHT	2980 x 1465 x 1850 mm (117.3 x 57.7 x 72.8 in)
WHEELBASE	1830 mm (72 in)
SEAT HEIGHT	445 mm (17.5 in)
GROUND CLEARANCE	260 mm (10.2 in)
FUEL TANK CAPACITY	26 L (6.86 gal)
CURB WEIGHT	560 kg (1235 lb) / LX model: 580 kg (1279 lb)
TOWING CAPACITY	400 kg (880 lb)
REAR BOX CAPACITY	150 kg (330 lb)

## TRANSMISSION

CV-TECH IBC clutch system	Primary and secondary variable transmission Gear box: L / H / N / R / P (parking lock shift system)
POWER TRAIN	2 wheel / 4 wheel drive, electric locking differential

## WHEELS

FRONT WHEELS	At Aluminum Alloy (14 x 7 in)
REAR WHEELS	At Aluminum Alloy (14 x 8 in)
FRONT TIRES	AT 26 x 9-14 (ABUZZ CST 6 ply rating)
REAR TIRES	AT 26 x 11-14 (ABUZZ CST 6 ply rating)

## SUSPENSION AND STEERING

FRONT SUSPENSION	Double wishbone independent suspension Hydraulic shock absorber with 5 spring preload adjustment
TRAVEL	180 mm (7.1 in)
REAR SUSPENSION	Double wishbone independent suspension Hydraulic shock absorber with 5 spring preload adjustment
TRAVEL	170 mm (6.7 in)
STEERING	Rack and pinion LX model: Rack and pinion, Electronic Power Steering (EPS)

## BRAKES

FRONT AND REAR BRAKE DISC SYSTEM

